



MADLOC T8 LED TUBES

New SINGLE-ENDED Power LED TUBES

NO RISK OF ELECTRIC SHOCK

COMPLIES with International Standard KEMA & ETIS

& Australian "Electrical Regulatory Authorities Council" (ERAC) recommendations.

- High Performance SMD LED's for controlled Color consistency
- Light Efficiency of the tube ≥95lm/w
- High Quality Aluminium Heatsink
- Advanced Thermal Technology used to remove heat
- CE & RoHS compliant
- Available with a Frosted lens cover
- · Small amount of re-wiring required
- Active & Neutral required at each tombstone
- Complies with **C** € ROHS
- Complete with a 3 year warranty

SPECIFICATIONS

Part No.	MADLED10WTC or F	MADLED18WTC or F	MADLED22WTC or F
Lumens	3k - 850l/m 5k - 900l/m	3k - 1650l/m 5k - 1700l/m	3k - 2000l/m 5k - 2050l/m
Beam Angle	120°	120°	120°
Power Factor	≥0.9	≥0.9	≥0.9
Power	10 watts	18 watts	22 watts
Length (A)	600mm	1200mm	1200mm
Lamp Life	50,000hrs	50,000hrs	50,000hrs
Diffuser	Frosted	Frosted	Frosted
CRI	≥80	≥80	≥80
Warranty	3 yr	3 yr	3 yr





12.7mm

Installation Instructions

Simply remove the old ballast & starter holder and wire both Active & Neutral to each tombstone.

The LED Tube requires BOTH Positive & Negative at both tombstones.

www.madloc.com.au

MADLOC LIGHTING 5/21 Babilla Close, Beresfield. NSW 2322 Ph: 0249 668 699 Fx: 0249 660 802

sales@madloc.com.au