



MADLOC LED INDUSTRIAL FLOODLIGHTS



MADLOC LODESTAR RANGE OF FLOODLIGHTS

Offering HIGH STABILITY due to it's UNIQUE Current Fluctuation Protection

- Can be installed in the harshest of conditions.
- CRI ≥80 provides high brightness for improved night vision
- Various Beam Angles available, 15° - 130°
- Reduces your Operating and Maintenance costs
- Suitable for ALL Floodlighting applications
- Lightweight Aluminium body
- Utilising CREE XT-E Chipset
- Certificates: ETC, CE, FCC, LVD, RoHS, DLC & LASER TESTING
- 50000hr rated LED lifetime
- Complete with a 3 YEAR warranty

SPECIFICATIONS

Part No.	MADFL46WLED	MADFL92WLED	MADFL145WLED	MADFL192WLED
Lumens	5100l/m	10200l/m	16800l/m	21000l/m
Beam Angle	130°	130°	130°	130°
Colour Temp	6000k	6000k	6000k	6000k
Power	46 watts	92 watts	145 watts	192 watts
Lumen Maintenance	50,000hrs	50,000hrs	50,000hrs	50,000hrs
Operating Temperature	-40°C to 50°C	-40°C to 50°C	-40°C to 50°C	-40°C to 50°C
IP Rating	IP68	IP68	IP68	IP68
Dimensions	L25xW23xD9cm	L32xW23xD9cm	L50xW23xD9cm	L50xW23xD15cm
Weight	5kg	6.5kg	8.7kg	11kg
Warranty	3 Years	3 Years	3 Years	3 Years