



MADLOC LED STREETLIGHT SERIES

MADLOC LODESTAR RANGE OF STREET LIGHTS

Offering HIGH STABILITY due to it's UNIQUE Current Fluctuation Protection

- Can be installed in the harshest of conditions.
- CRI ≥80 provides high brightness for improved night vision
- Reduces your Operating and Maintenance costs
- Suitable for ALL Street lighting and Parking applications
- Lightweight Aluminium body
- Utilising CREE XP-G Chipset
- Certificates: ETC, CE, FCC, LVD, RoHS, DLC & LASER TESTING
- 50000hr rated LED lifetime
- Complete with a 3 YEAR warranty

SPECIFICATIONS

Part No.	MADSTL46WLED	MADSTL92WLED	MADSTL145WLED	MADSTL192WLED
Lumens	5100l/m	10200l/m	16800l/m	21000l/m
Beam Angle	Type2, Short 130°	Type2, Short 130°	Type2, Short 130°	Type2, Short 130°
Colour Temp	5700k	5700k	6000k	6000k
Power	46 watts	92 watts	145 watts	192 watts
Lumen Maintenance	50,000hrs	50,000hrs	50,000hrs	50,000hrs
Operating Temperature	-40°C to 50°C	-40°C to 50°C	-40°C to 50°C	-40°C to 50°C
IP Rating	IP68	IP68	IP68	IP68
Spigot Diameter	62mm	62mm	62mm	62mm
Dimensions	L330xW224xD120	L440xW225xD120	L625xW225xD120	L621xW225xD150
Weight	5kg	6.5kg	8.7kg	11kg
Warranty	3 Years	3 Years	3 Years	3 Years